

BRADY B-612 OUTDOOR WHITE FILM

TDS No. B-612
Effective Date: 09/15/1998

Description:
Inkjet printable white film media

Details:

Box ID:
CPP FILM WP or CPP54 FILM WP

Use:
Pictorial images of high quality for outdoor display

Media Type:
Coated and filled polypropylene film

Characteristics:
Non-glare surface
Fast dry times

To be used with:
ColorPix™ 3600 System
ColorPix™ Pro 36 System
ColorPix™ Pro 54 System

Typical Weight:
53 lbs/3000 ft² (87g/m²)

Total thickness:
0.0054" (0.137 mm)

Material Length/Packaging Unit/Box:
24" x 85' x 2 rolls (610 mm x 26 meters)
36" x 111' x 1 roll (915 mm x 34 meters)
54" x 230' x 1 roll (1370 mm x 70 meters)

Image Durability:
3 months in outdoor use without a laminate. 12 months in outdoor use with outdoor ink and laminating film, sealed up both sides and at the edges. Life in use will be affected with finishing of printing surface and environmental conditions.

Shelf Life:
18 months in the conditions of 73°F (23°C) and 50 to 60% RH

Transportation Temperature:
5°F to 122°F (-15°C to 50°C)

Recommended Printing Temperature:
50°F to 91°F (10°C to 33°C)

Remarks:
Water droplets will make spots on the surface of printout and reduce quality. If printout is stored in high temperature and humidity, the printout tends to become slightly red in color. Do not pile up the printouts one on another. Do not use this media with indoor inks as bleeding will occur.

Trademarks:
ColorPix™ is a trademark of Brady Worldwide, Inc.

All U.S. Conventional Units are mathematically derived from the S.I. (metric) Units

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2016 Brady Worldwide, Inc. | All Rights Reserved
Material may not be reproduced or distributed in any form without written permission.

Brady North America | 6555 W. Good Hope Rd | Milwaukee, WI 53223 | USA | Tel: 414-358-6600 | Fax: 800-292-2289